

ZP2-LB

Addressable Fire Panel Accessory - Loop Expansion Printed Circuit Board - 2 loop

Overview

The loop board with plugable connectors adds 2 additional loops to your 2-loop low-end addressable fire panel that doubles the amount of devices to be supported by one panel and 128 extra zones can be programmed. Together with the 2 additional loops, 4 supervised sounder/fire-routing outputs, which can be used as freely programmable outputs, come along as well.

The Application

The loop board allows for bigger single panel applications. Instead of using two 2-loop panels you now have only one panel to power and all the loop wiring is concentrated to one location without having to use a Firenet network.

In case you need to expand an existing system you don't need to put another panel in place. You only have to add the loop board. This makes your system more flexible and easier to expand.

Please note that only the 2-loop panel has this capability of adding the additional loop board.

Mounting

The board can be plugged directly on the front of the main board of the panel on the easy to remove chassis. No additional cabling needs to be done.



Standard Features

- 2 loops and adds up to 128 zones
- 4 programmable outputs
- Plugable connectors
- Plugs directly on the front of the main board and chassis





Addressable Fire Panel Accessory - Loop Expansion Printed Circuit Board - 2 loop

Specifications

Programmable supervised	4, 700mA / 19.5-28VDC (24VDC nominal)	
Cable type	Recommended 2 core 1.5 mm² twisted pair	
End of Line resistor	15kohm	
.oops		
Outputs	2, 300mA@11VDC (peak 500mA@20V)	
Cable length	56ohm / 1microF max. 4 km	
Cable type	Recommended 2 core 1.5 mm² twisted pair	
invironmental conditions		
Storage temperature	-10°C to +50 °C	
Operating temperature	-8°C to +42 °C	
Relative humidity	max. 95 % (non-condencing)	
Mechanical		
Weight	0.12 kg	

Ordering Information

Part No.	Description
ZP2-LB	Addressable Fire Panel Accessory - Loop Expansion Printed Circuit Board - 2 loop